



## Nordmast klaasfiibrist lipumastide spetsifikatsioonid

		6m	7m	8m	9m	10m	12m	14m	14m split	16m split	18m split
Klaasfiibrist toru kaal	kg	9.0	10.0	12.0	14.5	20.5	26.0	44.0	61.0	71.0	81.0
Komplektse lipumasti kaal	kg	21.0	22.5	24.0	26.0	36.0	41.5	66.0	116.0	126.0	136.0
Tipu diameeter	mm	65	65	65	65	65	65	65	65	65	65
Põhja diameeter	mm	120	120	120	120	140	140	140	180	180	180
Klaasfiibri paksus +/- 0.5 mm	mm	3.5	3.5	3.5	3.5	4.0	4.0	5.0	5.0	5.0	5.0
Silindrilise osa pikkus	m	1	2	3	4	1	3	5	6	8	10
Jala terastoru pikkus	mm	500	500	500	500	600	600	1000	1000	1000	1000
Jala terastoru seinapaksus	mm	3.2	3.2	3.2	3.2	4.0	4.0	4.0	5.0	5.0	5.0
Jala terastoru diameeter	mm	101	101	101	101	121	121	121	159	159	159
Vundamendi soovitud sügavus	mm	800	800	800	900	1000	1200	1200	1400	1500	1500
Vundamendi soovitud diameeter	mm	300	300	300	300	400	400	500	600	600	600
Augu diameeter paigaldamisel kivisse	mm	25	25	25	25	25	25	25	25	25	25
Augu sügavus paigaldamisel kivisse	mm	300	300	300	300	400	400	400	500	500	500

Klaasplastist jala kate, kaal 0.8 kg, mõõdud 160 \* 355 mm